

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
24 September 2009 (24.09.2009)

PCT

(10) International Publication Number  
**WO 2009/117034 A2**

(51) International Patent Classification:

*B63C 11/02* (2006.01)      *B63C 11/18* (2006.01)  
*B63C 11/14* (2006.01)      *B63C 11/00* (2006.01)

(21) International Application Number:

PCT/US2008/087604

(22) International Filing Date:

19 December 2008 (19.12.2008)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/015,602    20 December 2007 (20.12.2007)    US  
12/338,944    18 December 2008 (18.12.2008)    US

(71) Applicant (for all designated States except US):

**PARAGON SPACE DEVELOPMENT CORPORATION** [US/US]; 3481 E. Michigan St., Tucson, AZ 85714 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **MACCALLUM, Taber, K.** [US/US]; 3481 E. Michigan St., Tucson, AZ 85714 (US). **ANDERSON, Grant, A.**; 3481 E. Michigan St., Tucson, AZ 85714 (US). **BOWER, Chad, E.** [US/US]; 3481 E. Michigan St., Tucson, AZ 85714 (US). **PADILLA, Sebastian, A.** [US/US]; 3481 E. Michigan St., Tucson, AZ 85714 (US).

(74) Agent: **VOLK, Michael, D., Jr.**; Stoneman Volk Patent

Group, 3770 N. 7th St., Suite 100, Phoenix, AZ 85014-5022 (US).

(81) Designated States (unless otherwise indicated, for every

kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every

kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— of inventorship (Rule 4.17(iv))

Published:

— without international search report and to be republished upon receipt of that report (Rule 48.2(g))

(54) Title: HAZARDOUS-ENVIRONMENTAL DIVING SYSTEMS

(57) Abstract: A system designed to increase diver safety in high-risk environments containing one or more hazardous materials. The system comprises one or more retrofittable kits enabling the upgrading of contaminate- vulnerable materials of an existing dive helmet to provide full environment isolation for the diver. The system preferably utilizes fluoroelastomeric replacement materials and components to convert an open circuit dive system to a closed circuit dive system. Methods of system development are also disclosed.



WO 2009/117034 A2

**HAZARDOUS-ENVIRONMENTAL DIVING SYSTEMS****BACKGROUND**

This invention relates to providing a system for improved hazardous-environmental diving systems. More particularly, this invention relates to providing systems designed to increase diver safety in high-risk environments.

Military and professional divers are frequently exposed to contaminated waters in the course of carrying out routine duties, as well as operations arising from acts of terrorism, accidents, and disaster recovery operations. During recovery from a terrorist attack, such as on the USS Cole, dive operations after a ship wreck or aircraft wreck often necessitate dive operations in mixtures of water and jet fuel, hydraulic fluid, or fuel oils.

Current diving equipment is not designed to adequately protect a diver from exposure to contaminants in the water. Many dive environments are so hazardous that existing diving equipment can deteriorate to the point of failure in a matter of minutes, especially when exposed to contaminants such as diesel oil. This exposes the diver to hazardous chemicals and compounds with adverse health effects, as well as threatening nominal operation of the very equipment on which the diver's life depends. Chemical warfare agent (CWA) contamination, biological warfare agents (BWA) and disease from pollution such as sewage in harbors are also of special concern; even low agent concentrations in the water are, in effect, amplified by the high pressure and full immersion conditions experienced by the diver.

In recent tests, industry standard dive helmets, including the popular Kirby-Morgan MK-21, equipped with double exhaust valves, failed to prevent intrusion of water and aerosols when the diver exhaled or when the diver's head moved from the upright position at any operational depth.

In addition to the immediate dangers present from terrorism, accident and disaster recovery operations, military and professional divers are frequently exposed to contaminated water in the course of carrying out routine duties. It is now evident that divers are at risk from chronic exposure to contaminated water in harbors, ports and waterways. Studies have shown that naval divers with multiple exposures to waterborne carcinogens are two times more likely to contract cancer than control populations.

The efforts to help in rescue and cleanup in Louisiana following Hurricane Katrina further illustrated problems related to the lack of "chemically hardened" dive equipment. Because industry-standard dive equipment is inadequately protective for use in chemically contaminated waters, responding divers working in the region reported delays to critical diving operations while evaluations of water conditions were completed.

Clearly, there exists an immediate need for improved “chemically hardened” dive hardware technology across the entire diving community. Furthermore, systems allowing the retrofitting and upgrade of existing dive hardware would provide a reasonably quick means for implementing such hazardous-environmental diving systems.

5

## OBJECTS AND FEATURES OF THE INVENTION

A primary object and feature of the present invention is to provide a system overcoming the above-mentioned problems.

It is a further object and feature of the present invention to provide such a system enabling upgrading of contaminate-vulnerable materials of a dive helmet with fluoroelastomeric materials.

10

It is another object and feature of the present invention to provide such a system enabling modifications for existing dive helmets to implement Return Surface Exhaust (RSE) technology.

It is a further object and feature of the present invention to provide such a system comprising one or more “retrofittable kits” comprising the above-described technologies and the related method of designing kits that fit new helmet models as they are developed.

15

It is another object and feature of the present invention to provide such a system, enabling protection of methods of use of such modified dive equipment within waters, requiring zero discharge of breathing gas into the aqueous medium.

A further primary object and feature of the present invention is to provide such a system that is efficient, inexpensive, and functional. Other objects and features of this invention will become apparent with reference to the following descriptions.

20

## SUMMARY OF THE INVENTION

In accordance with a preferred embodiment hereof, this invention provides a method related to retrofitting at least one existing underwater dive system to enhance the safety of at least one diver operating in waters containing at least one hazardous material, such as at least one existing underwater dive system comprising at least one existing dive helmet, at least one existing surface-supplied breathing-gas subsystem, at least one existing in-water exhaust subsystem, and at least one breathing environment available to the at least one diver, such method comprising the steps of: identifying at least one such existing underwater dive system comprising the at least one existing dive helmet, the at least one existing surface-supplied breathing-gas subsystem, and the at least one in-water exhaust subsystem; identifying, within the at least one existing underwater dive system, potential hazardous-material-caused failure points that result in at least one injurious introduction of at least one hazardous material into the at least one breathing environment during at least one operational duration; designing at least one risk-

30

mitigating modification to such at least one existing underwater dive system, such at least one risk-mitigating modification being structured and arranged to substantially mitigate risks associated with such hazardous-material-caused failure points identified to occur within the at least one operational duration; providing at least one retrofit kit comprising materials and procedures required to implement such at least one risk-mitigating modification to such at least one existing underwater dive system. Moreover, it provides such a method wherein the step of providing at least one risk-mitigating modification further comprises the step of integrating such at least one risk-mitigating modification into such at least one existing underwater dive system. Additionally, it provides such a method wherein the step of providing at least one risk-mitigating modification further comprises the step of: providing at least one soft-goods replacement for at least one existing hazardous-material-susceptible soft good experiencing exposure to the at least one hazardous material during the at least one operational duration; wherein the at least one soft-goods replacement comprises at least one hazardous-material-resistant composition; and wherein, within the at least one operational duration, such at least one hazardous-material-resistant composition is substantially resistant to degraded physical performance by contact with the at least one hazardous material, and transmission of hazardous quantities of the at least one hazardous material into the at least one breathing environment by permeation of the at least one hazardous material through such hazardous-material-resistant composition. Also, it provides such a method wherein such at least one hazardous-material-resistant composition comprises at least one fluoroelastomer. In addition, it provides such a method wherein the step of providing such at least one soft-goods replacement further comprises the step of integrating such at least one soft-goods replacement within such at least one existing underwater dive system. And, it provides such a method wherein the step of providing at least one risk-mitigating modification further comprises the steps of: providing at least one in-water-exhaust disabler to disable the at least one existing in-water exhaust subsystem; providing at least one surface-return exhaust subsystem structured and arranged to exhaust breathing gas from the at least one breathing environment of the at least one existing dive helmet to the surface; wherein at least one entry path for inhalable amounts of the at least one hazardous material may be removed. Further, it provides such a method wherein the surface-return exhaust subsystem comprises: at least one breathing-gas return hose structured and arranged to return breathing gas to the surface; at least one demand-based exhaust regulator structured and arranged to regulate, essentially on demand, exhausting of the breathing gas from the at least one breathing environment of the at least one existing dive helmet to such at least one breathing-gas return hose; and at least one exhaust coupler structured and arranged to operably couple such at least one demand-based exhaust

regulator to the at least one breathing environment of the at least one existing dive helmet; wherein at least one demand-based exhaust pathway may be established between the at least one breathing environment of the at least one existing dive helmet and the surface. Even further, it provides such a method wherein the surface-return exhaust subsystem further comprises:

5 between such at least one exhaust coupler and such at least one demand-based exhaust regulator, at least one over-pressure relief valve structured and arranged to relieve over pressures within the at least one breathing environment within the at least one existing dive helmet; and between such at least one exhaust coupler and such at least one demand-based exhaust regulator, at least one gas-flow control valve structured and arranged to control the routing of the breathing gas

10 between the at least one breathing environment of the at least one existing dive helmet, such at least one demand-based exhaust regulator, and such at least one breathing-gas return hose; wherein such at least one gas-flow control valve comprises at least one first flow setting to enable exhausting of the breathing gas from the at least one breathing environment of the at least one existing dive helmet to such at least one demand-based exhaust regulator, at least one second

15 flow setting to enable exhausting of the breathing gas from the at least one breathing environment of the at least one existing dive helmet directly to such at least one breathing-gas return hose without passage through such at least one demand-based exhaust regulator, and at least one third flow setting to enable exhausting of the breathing gas from the at least one breathing environment of the at least one existing dive helmet substantially entirely through such

20 at least one over-pressure relief valve by preventing exhausting of the breathing gas through such at least one demand-based exhaust regulator and such at least one breathing-gas return hose. Moreover, it provides such a method wherein the step of providing such at least one surface-return exhaust subsystem further comprises the steps of: providing at least one reduced-pressure source structured and arranged to provide at least one source of reduced atmospheric pressure;

25 providing at least one reduced-pressure communicator structured and arranged to establish fluid communication between such at least one reduced-pressure source and such at least one breathing-gas return hose; and providing at least one back-pressure regulator structured and arranged to regulate levels of reduced atmospheric pressure communicated between such at least one reduced-pressure source and such at least one breathing-gas return hose. Additionally, it

30 provides such a method wherein the step of providing such at least one surface-return exhaust subsystem further comprises the step of: providing at least one pressure indicator structured and arranged to indicate at least one pneumatic reference pressure, and at least one indication of pressure at such at least one demand-based exhaust regulator; and providing at least one breathing-gas monitor structured and arranged to monitor the breathing gas of the at least one

breathing environment for levels of the at least one hazardous material; wherein such at least one breathing-gas monitor comprises at least one breathing-gas sampling component structured and arranged to sample the breathing gas of the at least one breathing environment, at least one measurement component structured and arranged to measure the levels of the at least one hazardous material of the sampled breathing gas to determine if the levels of the at least one hazardous material fall within a preset range, and at least one hazardous-condition indicator structured and arranged to indicate to at least one system operator if the levels of the at least one hazardous material exceed the preset range. Also, it provides such a method wherein the step of providing such at least one surface-return exhaust subsystem further comprises the step of integrating such at least one surface-return exhaust subsystem within such at least one existing underwater dive system. In addition, it provides such a method wherein the step of providing at least one risk-mitigating modification further comprises the step of: providing at least one optical-faceplate covering structured and arranged to substantially cover at least one existing optical faceplate of the at least one existing dive helmet; wherein, within the at least one operational duration, such at least one optical-faceplate covering comprises at least one hazardous-material-resistant material substantially resistant to degraded physical performance by contact with the at least one hazardous material, and introduction of hazardous levels of the at least one hazardous material into the at least one breathing environment by permeation of the at least one hazardous material through such at least one hazardous-material-resistant material; and wherein such at least one hazardous-material-resistant material comprises sufficient transparency as to maintain a level of optical viewing through the at least one existing optical faceplate. And, it provides such a method wherein such at least one optical faceplate cover comprises at least one surface lamination of at least one glass material. Further, it provides such a method wherein the step of providing such at least one optical faceplate cover further comprises the step of integrating such at least one optical faceplate cover within such at least one existing underwater dive system. Even further, it provides such a method wherein the step of providing at least one risk-mitigating modification further comprises the step of: providing at least one chemical-resistant hose covering structured and arranged to cover the at least one existing breathing-gas supply hose; wherein the at least one chemical-resistant hose covering is structured and arranged to maintain the functional integrity of the at least one existing breathing-gas supply hose, within the at least one operational duration. Moreover, it provides such a method wherein the step of providing at least one mitigating modification further comprises the steps of modifying such at least one existing breathing-gas supply hose to comprise such at least one chemical-resistant covering. Additionally, it provides such a method wherein the step of providing at least one risk-

mitigating modification further comprises the step of: providing at least one helmet coating usable to coat at least one possibly-permeable outer-shell-portion of the at least one existing dive helmet; wherein such at least one helmet-coating is structured and arranged to reduce transmission of hazardous quantities of the at least one hazardous material into the at least one breathing environment by reducing contact interaction between the at least one hazardous material and the at least one possibly-permeable outer-shell-portion of the at least one existing dive helmet. Also, it provides such a method wherein the step of providing at least one risk-mitigating modification further comprises the step of: providing at least one replacement sealant structured and arranged to replace existing sealants of the at least one existing underwater dive system; wherein such at least one replacement sealant is structured and arranged to reduce transmission of hazardous quantities of the at least one hazardous material into the at least one breathing environment of the at least one existing dive helmet by permeation of the at least one hazardous material through such at least one replacement sealant. In addition, it provides such a method wherein such at least one replacement sealant comprises at least one room-temperature-cured fluoroelastomer-based composition. And, it provides such a method wherein the step of providing at least one risk-mitigating modification further comprises the step of integrating such at least one replacement sealant within such at least one existing underwater dive system.

In accordance with another preferred embodiment hereof, this invention provides a kit system related to retrofitting at least one existing underwater dive system to enhance the safety of at least one diver operating in waters containing at least one hazardous material, such at least one existing underwater dive system comprising at least one existing dive helmet, at least one existing surface-supplied breathing-gas subsystem, at least one existing in-water exhaust subsystem, and at least one breathing environment available to the at least one diver, such system comprising: at least one soft-goods replacement structured and arranged to replace at least one existing hazardous-material-susceptible soft good experiencing exposure to the at least one hazardous material during the at least one operational duration; wherein the at least one soft-goods replacement comprises at least one hazardous-material-resistant composition; and wherein, within the at least one operational duration, such at least one hazardous-material-resistant composition is substantially resistant to degraded physical performance by contact with the at least one hazardous material, and transmission of hazardous quantities of the at least one hazardous material into the at least one breathing environment by permeation of the at least one hazardous material through such hazardous-material-resistant composition. Further, it provides such a kit system wherein such at least one hazardous-material-resistant composition comprises at least one fluoroelastomer. Even further, it provides such a kit system further comprising: at

least one in-water-exhaust disabler structured and arranged to disable the at least one existing in-water exhaust subsystem; and at least one surface-return exhaust subsystem structured and arranged to exhaust breathing gas from the at least one breathing environment of the at least one existing dive helmet to the surface; wherein at least one entry path for inhalable amounts of the at least one hazardous material may be removed. Moreover, it provides such a kit system wherein such surface-return exhaust subsystem comprises: at least one breathing-gas return hose structured and arranged to return breathing gas to the surface; at least one demand-based exhaust regulator structured and arranged to regulate, essentially on demand, exhausting of the breathing gas from the at least one breathing environment of the at least one existing dive helmet to such at least one breathing-gas return hose; and at least one exhaust coupler structured and arranged to operably couple such at least one demand-based exhaust regulator to the at least one breathing environment of the at least one existing dive helmet; wherein at least one demand-based exhaust pathway may be established between the at least one breathing environment of the at least one existing dive helmet and the surface. Additionally, it provides such a kit system wherein such surface-return exhaust subsystem further comprises: between such at least one exhaust coupler and such at least one demand-based exhaust regulator, at least one over-pressure relief valve structured and arranged to relieve over pressures within the at least one breathing environment within the at least one existing dive helmet; and between such at least one exhaust coupler and such at least one demand-based exhaust regulator, at least one gas-flow control valve structured and arranged to control the routing of the breathing gas between the at least one breathing environment of the at least one existing dive helmet, such at least one demand-based exhaust regulator, and such at least one breathing-gas return hose; wherein such at least one gas-flow control valve comprises at least one first flow setting to enable exhausting of the breathing gas from the at least one breathing environment of the at least one existing dive helmet to such at least one demand-based exhaust regulator, at least one second flow setting to enable exhausting of the breathing gas from the at least one breathing environment of the at least one existing dive helmet directly to such at least one breathing-gas return hose essentially without passage through such at least one demand-based exhaust regulator, and at least one third flow setting to enable exhausting of the breathing gas from the at least one breathing environment of the at least one existing dive helmet substantially entirely through such at least one over-pressure relief valve by preventing exhausting of the breathing gas through aid at least one demand-based exhaust regulator and such at least one breathing-gas return hose. Also, it provides such a kit system wherein such at least one surface-return exhaust subsystem further comprises: at least one reduced-pressure source structured and arranged to provide at least one source of reduced

atmospheric pressure; at least one reduced-pressure communicator structured and arranged to establish fluid communication between such at least one reduced-pressure source and such at least one breathing-gas return hose; and at least one back-pressure regulator structured and arrange to regulate levels of reduced atmospheric pressure communicated between such at least one reduced-pressure source and such at least one breathing-gas return hose. In addition, it provides such a kit system wherein such at least one surface-return exhaust subsystem further comprises: at least one pressure indicator structured and arranged to indicate at least one pneumatic reference pressure, and at least one indication of operating pressure at such at least one demand-based exhaust regulator; and at least one breathing-gas monitor structured and arranged to monitor the breathing gas of the at least one breathing environment for levels of the at least one hazardous material; wherein such at least one breathing-gas monitor comprises at least one breathing-gas sampling component structured and arranged to sample the breathing gas of the at least one breathing environment, at least one measurement component structured and arranged to measure the levels of the at least one hazardous material of the sampled breathing gas to determine if the levels of the at least one hazardous material fall within a preset range, and at least one hazardous-condition indicator structured and arranged to indicate if the levels of the at least one hazardous material exceed the preset range. And, it provides such a kit system further comprising: at least one optical-faceplate cover structured and arranged to substantially cover at least one existing optical faceplate of the at least one existing dive helmet; wherein, within the at least one operational duration, such at least one optical-faceplate cover comprises at least one hazardous-material-resistant material substantially resistant to degraded physical performance by contact with the at least one hazardous material, and introduction of hazardous levels of the at least one hazardous material into the at least one breathing environment by permeation of the at least one hazardous material through such at least one hazardous-material-resistant material; and wherein such at least one hazardous-material-resistant material comprises sufficient transparency as to maintain a level of optical viewing through the at least one existing optical faceplate. Further, it provides such a kit system wherein such at least one optical faceplate cover comprises at least one glass material. Even further, it provides such a kit system further comprising: at least one chemical-resistant hose covering structured an arranged to cover the at least one existing breathing-gas supply hose; wherein such at least one chemical-resistant hose covering is structured an arranged to maintain the functional integrity of the at least one existing breathing-gas supply hose, within the at least one operational duration. Moreover, it provides such a kit system further comprising: at least one helmet coating structured and arranged to coat at least one possibly-permeable outer-shell-portion of the at least one existing

dive helmet; wherein such at least one helmet-coating is further structured and arranged to reduce transmission of hazardous quantities of the at least one hazardous material into the at least one breathing environment by reducing contact interaction between the at least one hazardous material and the at least one possibly-permeable outer-shell-portion of the at least one existing

5 dive helmet. Additionally, it provides such a kit system further comprising: at least one replacement sealant structured and arranged to replace existing sealants of the at least one existing commercial dive system; wherein such at least one replacement sealant is structured and arranged to reduce transmission of hazardous quantities of the at least one hazardous material into the at least one breathing environment of the at least one existing dive helmet by permeation

10 of the at least one hazardous material through such at least one replacement sealant. Also, it provides such a kit system wherein such at least one replacement sealant comprises at least one room-temperature-cured fluoroelastomer-based composition. In addition, it provides such a kit system wherein such at least one demand-based exhaust regulator comprises: at least one demand-based valve assembly structured and arranged to control, essentially on demand, passage

15 of the breathing gas through such at least one demand-based exhaust regulator; at least one valve housing structured and arranged to house such at least one demand-based valve assembly; at least one inlet duct structured and arranged to inlet the breathing gas, exhausted from the at least one breathing environment of the at least one existing dive helmet, to such at least one demand-based valve assembly; and at least one outlet duct structured and arranged to outlet the breathing

20 gas, from such at least one demand-based valve assembly, to such at least one breathing-gas return hose; wherein such at least one demand-based valve assembly comprises disposed between such at least one inlet duct and such at least one outlet duct, at least one valve seat, comprising a plurality of gas-conducting passages, structured and arranged to enable passage of the breathing gas therethrough, and in at least one superimposed placement adjacent such at least

25 one valve seat, at least one diaphragm structured and arranged to be in pressure communication with such at least one inlet duct, such at least one outlet duct and ambient water pressure; wherein such at least one diaphragm is flexibly movable between at least one flow-blocking position substantially engaging such at least one valve seat and at least one flow-delivery position disengaging such at least one valve seat; wherein, while in such at least one flow-

30 blocking position, such at least one diaphragm substantially blocks the passage of the breathing gas through such plurality of gas-conducting passages; wherein, while in such at least one flow-delivery position, such at least one diaphragm enables the passage of the breathing gas from such at least one inlet duct through such plurality of gas-conducting passages to such at least one outlet duct; and wherein exhausting of the breathing gas from the at least one breathing

environment applies a pressurizing bias force to such at least one diaphragm flexibly moving at least one portion of such at least one flexible diaphragm from such at least one flow-blocking position to such at least one flow-delivery position. And, it provides such a kit system wherein such at least one valve seat comprises: at least one central bore structured and arranged to be in fluid communication with such at least one inlet duct, such at least one central bore comprising at least one central axis; extending radially outward of such at least one central bore, at least one circumferential sealing surface structured and arranged to form at least one pressure seal with such at least one diaphragm; and at least one smooth-sweep transition-surface structured and arranged to provide at least one smoothly sweeping transition between such at least one central bore and such at least one circumferential sealing surface; wherein such plurality of gas-conducting passages are located within such at least one circumferential sealing surface. Further, it provides such a kit system wherein: each one of such plurality of gas-conducting passages comprises a hollow frustoconical aperture; each such hollow frustoconical aperture comprises at least one inlet diameter structured and arranged to minimize unsupported areas of such at least one diaphragm when such at least one diaphragm is in such at least one flow-blocking position, and at least one outlet diameter structured and arranged to beneficially optimize mass flow through such at least one valve seat. Even further, it provides such a kit system wherein such at least one diaphragm is further structured and arranged to generally conform to such at least one circumferential sealing surface when engaged with such at least one circumferential sealing surface. Even further, it provides such a kit system wherein such at least one diaphragm further comprises: at least one asymmetrical stiffener structured and arranged to structurally stiffen at least one portion of such at least one diaphragm; wherein such asymmetrical structural stiffening reduces the level of pressure forces required to flexibly move such at least one portion of such at least one flexible diaphragm from such at least one flow-blocking position to such at least one flow-delivery position.

In accordance with another preferred embodiment hereof, this invention provides a method, related to use of at least one existing commercial dive system to avoid health hazards relating to at least one diver operating in waters needed to be essentially uncontaminated, such at least one existing commercial dive system comprising at least one existing dive helmet, at least one existing demand-based breathing-gas supply subsystem, at least one existing in-water exhaust subsystem, and at least one breathing environment available to the at least one diver, such method comprising the steps of: identifying at least one such existing commercial dive system comprising the at least one existing dive helmet, the at least one existing demand-based breathing-gas supply subsystem, and the at least one in-water exhaust subsystem; and modifying

such at least one such existing commercial dive system by providing at least one in-water-exhaust disabler to disable the at least one existing in-water exhaust subsystem, and providing at least one surface-return exhaust subsystem structured and arranged to exhaust breathing gas from the at least one breathing environment of the at least one existing dive helmet to the surface;

5 wherein use of such at least one modified existing commercial dive system in such waters assists in avoiding water contamination relating to such exhaust breathing gas. In addition, it provides each and every novel feature, element, combination, step and/or method disclosed or suggested by this patent application.

#### BRIEF DESCRIPTION OF THE DRAWINGS

10 FIG. 1 shows a schematic diagram, generally illustrating an existing dive system modified to comprise retrofits designed to enhance diver safety during operation in waters containing at least one hazardous material, according to a preferred embodiment of the present invention.

FIG. 2 shows a perspective view illustrating an existing dive helmet modified to  
15 comprise a hazardous environment modification assembly, according to a preferred embodiment of the present invention.

FIG. 3 shows an exploded perspective view, illustrating preferred subcomponents of the hazardous environment modification assembly including a return surface exhaust assembly, according to the preferred embodiment of FIG. 1.

20 FIG. 4 shows a perspective view, illustrating the return surface exhaust assembly (apart from the dive helmet) according to the preferred embodiment of FIG. 1.

FIG. 5 shows an exploded perspective view of the Demand Exhaust Regulator (DER) according to the preferred embodiment of FIG. 1.

25 FIG. 6A shows a perspective view, in partial section, of the Demand Exhaust Regulator (DER), according to the preferred embodiment of FIG. 1.

FIG. 6B shows a top view of a preferred valve seat of the Demand Exhaust Regulator of FIG. 6A.

FIG. 6C shows a sectional view through the section 6C-6C of FIG. 6B illustrating preferred arrangements of the valve seat of FIG. 6A.

30 FIG. 7 shows a perspective view, of a valve body of the Demand Exhaust Regulator (DER), according to the preferred embodiment of FIG. 1.

FIG. 8 shows a top view of the valve body of FIG. 7.

FIG. 9 shows a sectional view through the section 9-9 of FIG. 8.

FIG. 10 shows a sectional view, through the section X-X of FIG. 3, illustrating an emergency dump valve in a normal operating configuration.

FIG. 11 shows a sectional view, through the section X-X of FIG. 3, illustrating the emergency dump valve in an emergency configuration.

5 FIG. 12 shows a schematic diagram, illustrating preferred arrangements of a surface-return subassembly, according to the preferred embodiment of FIG. 1.

FIG. 13 shows a flow diagram illustrating a preferred method of using a retrofitted underwater dive system to avoid health hazards relating to special diving operations, according to a preferred method of the present invention.

10 FIG. 14 shows a flow diagram illustrating a preferred method of retrofitting an existing underwater dive system to avoid health hazards relating to special diving operations, according to a preferred method of the present invention.

#### DETAILED DESCRIPTION OF THE BEST MODES

#### AND PREFERRED EMBODIMENTS OF THE INVENTION

15 FIG. 1 shows a schematic diagram, generally illustrating preferred arrangements of Hazardous Material-hardened Regulated Surface Exhaust Diving System (HMRSEDS) **300**, according to a preferred embodiment of the present invention. Preferred embodiments of hazardous-environmental diving system **100**, preferably including HMRSEDS **300**, are preferably generated by applying one or more specific modifications to an existing underwater  
20 dive system **101**, preferably using a component-based kit system identified herein as Hazardous Environment Modification Assembly (HEMA) **102**. HEMA **102** is preferably adapted to implement one or more risk-mitigating modifications to the diver-worn equipment of existing underwater dive system **101**. In HMRSEDS **300**, HEMA **102** is preferably used to convert a commercially available dive helmet **103** into a fully encapsulated protection system to isolate the  
25 diver from hazardous diving environment **111** containing hazardous materials **109**.

The following descriptions generally describe HMRSEDS **300** in terms of a full implementation of HEMA **102**. Upon reading this specification, those with ordinary skill in the art will appreciate that, under appropriate circumstances, other system arrangements such as, for example, applying each of the below-described kit-based modifications separately, as indicated  
30 by a specific helmet design or severity of operational hazard, or implementation in whole, thus ensuring maximum protection of the diver during use, etc., may suffice. It is further noted that each of the below-described modifications enabled by HEMA **102** are intended to be installable by the end users of the underwater diving systems.

For general-use embodiments of hazardous-environmental diving system **100**, a broad resistance to many types of chemical hazards is preferred, especially a resistance to chemicals that are most likely to be found in a waterway spill. Resistance to fuels and oils, industrial chemicals, biological agents, and acids and bases are noted examples of chemicals which have  
5 been observed to degrade the helmet materials resulting in leaks or other detrimental changes in the helmet and its components.

The full range of potential hazardous materials **109** within hazardous diving environment **111** is extensive, frequently including chemicals, biological vectors, toxic industrial chemicals, toxic industrial materials (TIC/TIM) and potential chemical warfare agent (CWA) contaminants.  
10 Of special concern is that low contaminant concentrations in the breathing air system result in high partial pressures of the contaminant at working depths. Thus, even small amounts of hazardous materials **109** in the water, such as jet fuel or other chemical agents, can be toxic to divers submerged at working depth. An essential step in the protecting of a diver is to remove any pathway in which contaminants could enter the helmet or suit. The preferred embodiments  
15 of hazardous-environmental diving system **100** are preferably designed to modify existing underwater dive systems **101** with the intent of ensuring the maintenance of safe breathing environments during at least one operational duration.

HEMA **102** is a user-retrofittable kit preferably designed to retrofit at least one surface-supplied diving apparatus, identified herein as existing underwater dive systems **101**. Prior to  
20 modification by HEMA **102**, such diving apparatus is configured to supply breathing gas to the diver by way of supply umbilical **105** and for the breathing gas to be subsequently discharged directly into the surrounding hazardous diving environment **111** (without a surface return). Such existing underwater dive systems **101** preferably comprise at least one existing demand-type dive helmet **103**, at least one existing surface-supplied breathing-gas subsystem **112**, and at least one  
25 existing in-water exhaust subsystem **114** (shown in FIG. 1 removed from dive helmet **103**).

Preferably, any significant operational safety and performance deficiencies, within the components of existing underwater dive systems **101**, are identified and preferably corrected with one or more risk-mitigating modifications provided by integration in the preferred structures and arrangements of HEMA **102**. Substantially all risk-mitigating modifications are  
30 preferably designed to protect the diver from the intrusion of hazardous materials **109** into the breathing environment for at least one predetermined operational duration, as further described below.

HEMA **102** is preferably designed to resolve at least two critical-risk issues within existing underwater dive system **101**. First, HEMA **102** addresses the movement of

contaminants through material boundaries of the diver's breathing environment. Secondly, HEMA **102** is preferably designed to eliminate back contamination of aerosols, fumes, and particulates generated from the in-water exhausting of breathing gas from existing in-water exhaust subsystem **114**.

5           Testing by the applicant clearly demonstrated that the most commonly used existing underwater dive systems **101**, as currently designed, do not adequately protect divers against the most common contaminants and solvents. Preferred test durations were designed to simulate operational durations of not less than 6 hours. Such testing preferably included both the demand supply regulator **107**, internal exhaust valves, and related components of dive helmet **103**. The testing identified multiple hazardous-material-caused failure points within existing underwater  
10           dive system **101** that resulted in at least one injurious introduction of hazardous materials **109** into the diver's breathing environment. For example, permeability testing of the existing second-stage regulator diaphragm of demand supply regulator **107** (and associated parts) showed a serious failure of the Silicone materials when exposed to low molecular weight constituents of  
15           Jet A fuel, among other contaminants. In a diesel-fuel environment, the existing helmet systems experienced deterioration of the diaphragms and o-rings within 5-15 minutes. It is noted that breakthrough of carcinogenic compounds into the diver's breathing environment was observed to occur substantially concurrently with such failures.

          In selecting appropriate replacement materials, applicant identified resistance to chemical  
20           attack and resistance to permeability as two primary considerations. As testing by applicant clearly illustrated, many customary helmet materials are vulnerable to direct chemical degradation. Testing also produced an unexpected finding; many materials can exhibit satisfactory resistance to direct chemical attack, but still allow the chemical to migrate through the composition, thus allowing a chemical pathway to compromise the diver's safety.

25           Materials identified in the testing and analysis to be especially susceptible to chemical attack and permeability where the existing soft-goods components **106** of dive helmet **103**. These preferably include elastomeric (natural or synthetic rubber) O-rings, diaphragms, seals, gaskets, etc. As a result, HEMA **102** preferably comprises at least one soft-goods replacement package **120** preferably comprising a plurality of soft goods replacement parts for the soft  
30           (elastomeric) materials subjected to in-service contact with hazardous materials **109**.

          Elastomeric replacement components **110** of soft-goods replacement package **120** preferably comprise materials exhibiting equivalent mechanical characteristics to the original parts, with the added characteristic of low chemical permeability (thus reducing the permeation of hazardous materials **109** into the breathing gas).

Preferably, replacement components **110** of soft-goods replacement package **120** include one-to-one replacements of the existing Buna-N (nitrile rubber), neoprene, butyl, and silicon parts.

Typically, each commercial dive helmet **103** comprises a model-specific arrangement of existing soft-good components **106**. To facilitate installation of replacement components **110**, soft-goods replacement package **120** preferably comprises an equivalent “model-specific” set of replacement components **110**. For example, in a highly preferred embodiment of HMRSEDS **300**, existing underwater dive systems **101** preferably comprise a model 37 commercial dive helmet **103** produced by Kirby Morgan Dive Systems Inc. of Santa Maria, CA. Preferred replacement components **110** of soft-goods replacement package **120** are preferably selected based to match the size, required quantity, and mechanical properties of the existing soft-goods components **106** of this helmet. Prior to modification, the model 37 helmet contains well over two dozen O-rings, gaskets, and seals. It is noted that specific helmet data, including exploded views and part schedules containing a full list of existing soft-good components **106** used within this and other preferred models, is publicly available for download by accessing the manufacturer’s internet website (currently located at URL [http:// www.kirbymorgan.com](http://www.kirbymorgan.com)).

Preferably, components of soft-goods replacement package **120** comprise one or more elastomers of low chemical permeability, good off-gassing characteristics, and appropriate mechanical properties. In addition, such hazardous-material-resistant compositions are preferably resistant to degraded physical performance by contact with hazardous materials **109**, and transmission of hazardous quantities of hazardous materials **109** into the breathing environment by permeation of hazardous materials **109** through such hazardous-material-resistant elastomers.

Through extensive analysis and testing, applicant determined that a specific class of elastomeric materials produced replacement components **110** of superior performance. These replacement components **110** were preferably fabricated from a class of elastomers based on fluorine chemistry, preferably fluorocarbon elastomers based on fluorinated organic polymers having carbon-to-carbon linkages as the foundation of their molecular structures. These materials, generally identified in the art as fluoroelastomers (FKM), exhibit high chemical resistance, suitable mechanical properties, and acceptable material cost. The selected FKM materials were found to produce replacement components with substantially equivalent mechanical properties to those of the manufacturer’s existing soft-goods components **106**, thus maintaining critical performance specifications within the diving equipment. Materials comprising a range of fluoroelastomer chemistries may be selected to align with the required

mechanical properties and or chemical resistance requirements of a specific replacement components **110**. Preferred replacement components **110** of preferred embodiments of soft-goods replacement package **120** preferably included O-rings and diaphragms, seals, and gaskets. FKM sealants, calking and coatings are also preferably used, as further described below.

5 In general, fluoroelastomer permeability is inversely proportional to the fluorine content of the material. Therefore, chemical permeability is also inversely proportional to material cost. A fluoroelastomer material, preferred for use in the development of a lower-cost soft-goods replacement package **120**, preferably comprises commercially available Viton® products produced by DuPont Performance Elastomers L.L.C. of Wilmington, Delaware. The original  
10 commercial fluoroelastomer, Viton A, is preferred for general use in such a general purpose package.

Alternately preferably, a second fluoroelastomer material, preferred for use in the development of high-performance soft-goods replacement packages **120**, preferably comprises replacement parts comprised of Kalrez® perfluoroelastomer, which is produced by DuPont  
15 Performance Elastomers L.L.C. Kalrez® demonstrated the lowest permeability and degradation rate of all materials tested by applicant, but also comprised a higher cost than Viton A. A demand regulator diaphragm comprising Kalrez® was found to have contributed only 12 parts per trillion of hydrocarbons to the breathing gas when diving in pure Jet A after 1,125 hours of testing. While the cost of Kalrez® is higher per installation, the reduced equipment rebuilding  
20 frequency is anticipated to more than compensate for the added initial cost. Table A of the specification provides a summary of preferred FKM materials and material sources for various replacement components **110** of soft-goods replacement packages **120**. Upon reading the teachings of this specification, those of ordinary skill in the art will now understand that, under appropriate circumstances, considering such issues as intended use, nature of hazardous diving  
25 environment, etc., other elastomer selections, such as Xyfluor® (Green and Tweed), Dyneon® (by 3M), Nitrile, etc., may suffice.

**TABLE A**

• DuPont PE: Viton Sheet (diaphragm material, etc.)
• AAA Acme Rubber Co.: Viton sheet, custom molding, and other extrusions
• Eagle Elastomer, Inc.: Viton Sheet and other extrusions
• Parco Inc.: Viton custom molded parts and o-ring manufacturer
• Simrit (Simrit USA): Viton custom molded parts and o-ring manufacturer

<ul style="list-style-type: none"> <li>• Fluorolast: Fluoroelastomer caulk and sealants</li> </ul>
<ul style="list-style-type: none"> <li>• Pelseal® Technologies, LLC: Fluoroelastomer caulks and sealants (Used to seal joints in the of dive helmet <b>103</b>)</li> </ul>
<ul style="list-style-type: none"> <li>• DuPont PE: Krytox performance lubricants.</li> </ul>

In popular commercial dive helmets, such as those produced by the Kirby Morgan Dive Systems, Inc. of Santa Maria CA, the existing face-port lens **131** is constructed of clear polycarbonate. This material has been identified as having a moderate to high potential for contaminate permeation and is easily damaged by contact with a number of hazardous materials **109**. Therefore, preferred embodiments of HEMA **102** further preferably comprise at least one optical-faceplate covering **133** structured and arranged to substantially cover existing face-port lens **131**, as shown. Preferably, optical-faceplate covering **133** comprises at least one hazardous-material-resistant material substantially resistant to degraded physical performance by contact with hazardous material **109** and introduction of hazardous levels of hazardous material **109** into the breathing environment by permeation.

Preferably, optical-faceplate covering **133** comprises sufficient transparency as to maintain a level of optical viewing through the existing face-port lens **131**. Most preferably, optical-faceplate covering **133** comprises a sheet of glass material laminated to the exterior surface of the existing face-port lens **131**.

Surface-supplied breathing-gas subsystem **112** preferably comprises supply control station **116** and supply umbilical **105**, as shown. A typical supply umbilical **105** preferably consists of a 3/8" (minimum) breathing-gas supply hose **122**, a 1/4" pneumofathometer hose, and a communication cable. Critical components of supply umbilical **105** having a potential hazardous-material-caused failure include the rubber or synthetic composition of the existing breathing-gas supply hose **122**. Such hoses comprise a similar susceptibility to certain hazardous materials **109** as do the soft goods of dive helmet **103**, including permeation of hydrocarbons into the breathing air supply. To mitigate the risk of chemical intrusion, HEMA **102** preferably comprises at least one chemical-resistant hose covering **118** structured an arranged to cover the existing breathing-gas supply hose of supply umbilical **105**. Preferably, chemical-resistant hose-covering **118** is structured an arranged to maintain the functional integrity of the existing breathing-gas supply hose **122** (within the intended operational duration). Most preferably, chemical-resistant hose-covering **118** comprises at least one flouoroelastomer sheath **124** wrapped around existing breathing-gas supply hose **122** and sealed with flourelastomer sealant **126**, as shown. Upon reading the teachings of this specification, those of ordinary skill in the art will

now understand that, under appropriate circumstances, considering such issues as cost, intended use, etc., other supply-hose arrangements, such as the use of umbilical hoses comprising chemical resistant fluoroelastomers, the use of other protective surface coatings, etc., may suffice.

5 Preferably, supply control station **116** comprises a commercially available unit providing a control point for a topside operator (tender) and one or more surface-supported divers. Diving control station **116** preferably comprises provisions for the control of the supply of breathing gas, diver depth monitoring, and voice communications. Preferably, supply control station **116** is located outside of hazardous diving environment **111**, such as, for example, at the surface of the  
10 water, in a diving bell, or in a submerged habitat within hazardous diving environment **111**. The breathing gas supplied by standard umbilical **105** preferably comprises air or other gas mixtures (e.g. helium/oxygen, etc.). A preferred commercial supply control station suitable for use as supply control station **116** includes the Kirby Morgan model KMACS-5.

HEMA **102** further comprises a preferred means for eliminating back contamination of  
15 aerosols, fumes, and particulates entering from the in-water exhausting of breathing gas from existing in-water exhaust subsystem **114**. This preferred risk-mitigating modification is preferably achieved by removal of the existing in-water exhaust subsystem **114** and replacement with Regulated Surface Exhaust (RSE) assembly **104**, as described below.

FIG. 2 shows a perspective view illustrating an existing dive helmet **103** modified to  
20 comprise HEMA **102**, according to a preferred embodiment of the present invention. FIG. 3 shows an exploded perspective view, illustrating preferred hardware components of HEMA **102**, according to the preferred embodiment of FIG. 1.

Preferably, dive helmet **103** comprises an existing commercial dive helmet, or alternately preferably, an equivalent military version. Such existing dive helmets preferably include, for  
25 example, the model SuperLite®-17B (and the U.S. Navy version of the commercial Kirby Morgan superlite 17B helmet known as the MK-21), the larger Kirby Morgan® 37, and the SuperLite®-27, each produced by Kirby Morgan Dive Systems, Inc. of Santa Maria CA. The Kirby Morgan dive helmets are among the most widely used designs in surface-supplied diving operations and are considered standard dive equipment in the commercial diving industry.

30 As noted previously, testing of the unmodified MK-21 helmets failed to prevent intrusion of water when a diver's head moved from the upright position at any operational depth, despite being equipped with an in-water exhaust subsystem **114** having a double exhaust valve. Contamination of the breathing environment within the helmet often results in reduced dive duration, at a minimum, and may result in immediate abort due to equipment failure (due to

material deterioration). Furthermore, the inhalation of contaminated microscopic water droplets from the exhaust circuit of the existing in-water exhaust subsystem **114** provides a direct passage of the contaminant to the diver's lungs, and thus to the bloodstream.

5 The retrofitting of RSE assembly **104** preferably eliminates in-water exhaust subsystem **114** by returning the exhaled breathing gas to the surface, absolutely preventing back contamination by aerosols, fumes, particulates, etc. In addition, this preferred risk-mitigating modification allows for continuous monitoring of the exhaust gas for indications of a breach in any part of the now fully sealed and isolated breathing gas system.

10 The following descriptions provide a general overview of the removal of in-water exhaust subsystem **114**, preparation of dive helmet **103** for retrofitting, and installation of RSE assembly **104** to dive helmet **103**.

15 The outer shell **128** of dive helmet **103** is the central structure for mounting all the components that make up the complete helmet. The preferred Kirby Morgan helmets described herein are generally designed to allow easy replacement of parts, making the retrofitting of the helmet, using the preferred kit embodiments described herein, within the capabilities of individuals of ordinary skill in the art.

20 The preferred outer shell **128** comprises a lightweight glass-fiber reinforced thermal setting polyester (fiberglass) with carbon fiber reinforcements and a gel coat finish. Alternately preferably, outer shell **128** may comprise a non-corrosive metal composition (such as provided within the stainless steel Kirby Morgan 77 helmet).

25 Depending on the permeability of the outer shell **128**, an additional chemical-resistant coating **130** may be applied to outer shell **128** during preferred retrofit preparation procedures (at least embodying herein at least one helmet coating structured and arranged to coat at least one possibly-permeable outer-shell-portion of the at least one existing dive helmet, wherein such at least one helmet-coating is further structured and arranged to reduce transmission of hazardous quantities of the at least one hazardous material into the at least one breathing environment by reducing contact interaction between the at least one hazardous material and the at least one possibly-permeable outer-shell-portion of the at least one existing dive helmet).

30 Preferably, the standard side-block valve-assembly **132**, bent tube **134**, and demand supply regulator **107** of dive helmet **103** are retained in the preferred embodiments of hazardous-environmental diving system **100** (see FIG. 1). Preferably, each of the above-described components are modified, preferably using appropriate FKM components of soft-goods replacement package **120**, to replace any existing soft-goods components **106** identified as being incompatible with operation in hazardous diving environment **111**. These modifications

specifically include the replacement of the existing silicone regulator diaphragm of demand supply regulator **107** (and associated parts) with an FKM equivalent replacement component **110**. In addition, as part of a preferred retrofit procedure, the standard side-block valve-assembly **132**, bent tube **134**, and demand supply regulator **107** may be removed from outer shell **128** to allow for the replacement of standard silicone “pass-through” sealants with an appropriate flourelastomer sealant **126**, preferably at least one room temperature-cured flouroelastomer (at least embodying herein at least one replacement sealant structured and arranged to replace existing sealants of the at least one existing commercial dive system, wherein such at least one replacement sealant is structured and arranged to reduce transmission of hazardous quantities of the at least one hazardous material into the at least one breathing environment of the at least one existing dive helmet by permeation of the at least one hazardous material through such at least one replacement sealant, and wherein such at least one replacement sealant comprises at least one room temperature-cured flouroelastomer-based composition).

The chemically-hardened side-block valve-assembly **132** preferably retains the functions of receiving the main gas supply flow from supply umbilical **105**, supporting at least one non-return valve, providing fittings/controls for an emergency gas supply, providing fittings/controls for ventilation and defogging (supplying a flow of air to the helmets air train assembly), and provides a pathway for breathing gas routed to the chemically-hardened demand supply regulator **107**. The chemically-hardened demand supply regulator **107** preferably retains the function of sensing the start of the diver’s inhalation and opening the supply regulator diaphragm (essentially on demand) to inlet the breathing gas to the oral-nasal mask within the helmet.

In an unmodified helmet, as the diver exhales, the supply regulator diaphragm of demand supply regulator **107** closes causing the exhalation gas to flows through the regulator exhaust and the helmet exhaust into exhaust subsystem **114**. Exhaust subsystem **114** (preferably comprising the Kirby Morgan Quad-Valve™ exhaust assembly) is designed to route the exhaust of demand supply regulator **107** and the helmet main exhaust to either one of two (or both) exhaust valves that are part of the bubble deflecting whiskers, and out into the water. Additional information relating to the Kirby Morgan Quad-Valve™ exhaust assembly is presented in Kirby Morgan Document 071031002, publicly available for download at manufacturer’s internet website (URL [http:// www.kirbymorgan.com](http://www.kirbymorgan.com)).

As empirical testing demonstrated the inability of exhaust subsystem **114** to fully eliminate back contamination during operation, it is preferred that exhaust subsystem **114** be completely removed from the breathing system of dive helmet **103** (as shown in FIG. 1). The return-to-surface exhaust functions provided by RSE assembly **104** preferably replaces the in-

water exhaust functions eliminated by the removal of exhaust subsystem **114**. Detailed instructions for the removal of exhaust subsystem **114** is presented in Kirby Morgan Document #071031002, Chapter 7.0 entitled “Breathing System Maintenance and Repairs”.

5 Preferably, the retrofitting of RSE assembly **104** to dive helmet **103** converts existing underwater dive system **101** to a closed-circuit breathing system whereby the diver’s exhausted gas is returned to the surface and exhausted to the atmosphere rather than exhausting into the water. The above-described modifications at least embody herein at least one in-water-exhaust disabler structured and arranged to disable the at least one existing in-water exhaust subsystem (by means of removal), and at least one surface-return exhaust subsystem structured and  
10 arranged to exhaust breathing gas from the at least one breathing environment of the at least one existing dive helmet to the surface (wherein at least one entry path for inhalable amounts of the at least one hazardous material may be removed).

It is again noted that the term “surface” shall include breathable atmospheres outside hazardous diving environment **111**, such as the surface of the water, a diving bell, or a  
15 submerged habitat within hazardous diving environment **111**.

FIG. 4 shows a perspective view, illustrating RSE assembly **104** of HEMA **102** (apart from the dive helmet) according to the preferred embodiment of FIG. 1. Reference is now made to FIG. 4 with continued reference to FIG. 1 through FIG. 3.

RSE assembly **104** preferably comprises two component assemblies generally identified  
20 herein as helmet-mounted subassembly **140** and surface-return subassembly **142**, as shown (see also FIG. 1). Helmet-mounted subassembly **140** preferably comprises exhaust plenum **144**, exhaust plenum cover plate **145**, emergency dump valve **146**, first connector tube **148**, three-way bypass valve **150**, bypass flow fuse **152**, Demand Exhaust Regulator (DER) **154**, and second connector tube **156**, as shown. In addition, helmet-mounted subassembly **140** preferably  
25 comprises support plate **157** to support DER **154** from outer shell **128** and a plurality of connector fittings **160** adapted to couple the various components within the exhaust flow path. It is noted that exhaust plenum cover plate **145** has been omitted from the view of FIG. 4 to assist in the description of the interior arrangements of exhaust plenum **144**. In an alternate preferred embodiment of helmet-mounted subassembly **140**, to reduce the potential for leakage, all  
30 connector tubing between exhaust plenum **144** and breathing-gas return hose **170** comprises welded fittings.

Preferably, exhaust plenum **144** is designed to couple the existing regulator exhaust port **162** of demand supply regulator **107** with the existing helmet main exhaust **164** within a single plenum chamber **166** (at least embodying herein at least one exhaust coupler structured and

arranged to operably couple such at least one demand-based exhaust regulator to the at least one breathing environment of the at least one existing dive helmet), as shown. Exhaust plenum **144** is preferably mounted between demand supply regulator **107** and main exhaust body (Kirby Morgan part number 123 of the model 37 helmet of Kirby Morgan Document #07080003).

5 Preferably, the upper wall of exhaust plenum **144** mates to the regulator exhaust flange of demand supply regulator **107**, as shown. The rear wall of exhaust plenum **144** preferably mates to the main exhaust body of the helmet, as best shown in FIG. 2. Preferably, one or more flourelastomer sealing materials are used to seal exhaust plenum **144** to the adjacent structures. Preferably, both emergency dump valve **146** and first connector tube **148** mount to exhaust  
10 plenum **144** and are preferably in fluid communication with plenum chamber **166**, as shown.

Preferably, emergency dump valve (EDV) **146** is structured and arranged to provide emergency pressure relief due to over pressurization of the helmet (or emergency exhaust to ambient due to catastrophic failure of the return system). The preferred structures and features of EDV **146** are further described in FIG. 10 and FIG. 11.

15 In normal operation, exhaust gases preferably exit plenum chamber **166** through first connector tube **148** and are preferably conducted to three-way bypass valve **150**, as shown. Preferably, three-way bypass valve **150** (at least embodying herein at least one gas-flow control valve) is structured and arranged to control the routing of the exhaust gas between the breathing environment of dive helmet **103**, DER **154**, and at least one surface-return hose **170** of surface-  
20 return subassembly **142** (see also FIG. 1).

Preferably, a diver at depth can set three-way bypass valve **150** to one of three operational settings using handle **151**. Preferably, three-way bypass valve **150** comprises a normal-operational setting to enable exhausting of the breathing gas from the breathing environment of dive helmet **103** through DER **154**. In addition, three-way bypass valve **150**  
25 preferably comprises a free-flow setting to enable exhausting of the breathing gas from dive helmet **103** directly to surface-return hose **170** without passage through DER **154**. This setting may be selected by the diver in the event of a failure of DER **154**. The third flow setting preferably disables the return-to-surface exhaust circuit by isolating the dive helmet **103** from both DER **154** and surface-return hose **170**. The diver, in the event of a significant failure of the  
30 surface return exhaust system, may select this setting to prevent a dangerous loss of pressure within the helmet. In the third setting, exhausting of the breathing gas preferably occurs substantially entirely through EDV **146**.

In the free-flow setting, second connector tube **156** preferably functions as a means for conducting the exhaust gas diverted by three-way bypass valve **150** directly to surface-return

hose **170**, as shown. Bypass flow fuse **152** is preferably located “in-line” with the exhaust flow of second connector tube **156** and is preferably positioned between 45-degree compression adapter **172** and coupling **174**, as shown. Preferably, bypass flow fuse **152** is adapted to inhibit sudden rapid gas flow as a result of the development of a sudden pressure differential, across the fuse, which exceeds preset limits. Such a pressure differential may be a result of a downstream component failure within surface-return subassembly **142**, such as a line rupture within surface-return hose **170**. Bypass flow fuse **152** is essentially a check valve preferably installed in between dive helmet **103** and surface-return hose **170** to immediately inhibit flow upon sensing a pressure differential across the fuse that exceeds the setpoint.

The exhaust pathway extending from exhaust plenum **144** preferably comprises a minimum cross-sectional diameter of about 3/4 inch. This preferred minimum diameter was found to assist in maintaining acceptable levels of resistive breathing effort within the overall system (substantially equivalent to the original in-water exhaust arrangements).

FIG. 5 shows an exploded perspective view of DER **154** according to the preferred embodiment of FIG. 1. FIG. 6 shows a perspective view, in partial section, of DER **154**. FIG. 7 shows valve body **172** of DER **154**. FIG. 8 shows a top view of valve body **172**. FIG. 9 shows a sectional view through the section 9-9 of FIG. 8.

DER **154** preferably functions as a pressure-actuated valve that enables controlled exhaust from helmet-mounted subassembly **140** to surface-return subassembly **142**. DER **154** preferably comprises a generally cylindrical valve housing **182** preferably adapted to house at least one internal demand-based valve assembly **180**, as shown. Preferably, demand-based valve assembly **180** is structured and arranged to control, essentially on demand, passage of the breathing gas through DER **154**, thus maintaining a relatively static pressure equilibrium within dive helmet **103**. Demand-based valve assembly **180** preferably comprises a generally circular valve seat **190** and exhaust diaphragm **192** in a superimposed placement adjacent valve seat **190**, as shown.

Valve housing **182** preferably comprises inlet duct **184** to inlet the breathing gas exhausted from dive helmet **103** (preferably via exhaust plenum **144**, first connector tube **148**, and three-way bypass valve **150** respectively). Inlet duct **184** of valve housing **182** is preferably arranged to conduct the exhausted breathing gases from a side-positioned entry point on valve housing **182**, turning upward through central bore **195** to the internally located demand-based valve assembly **180**, as shown. Valve housing **182** preferably comprises a corresponding outlet duct **186** to outlet the exhausted breathing gases, from the interior of valve housing **182** after controlled passage through demand-based valve assembly **180**.

Valve seat **190** is preferably disposed between inlet duct **184** and outlet duct **186** and preferably forms the upper portion of central bore **195**, as shown. Preferably, valve seat **190** comprises a circumferential sealing surface **200** extending radially outward from central axis **202** of central bore **195**, as shown. The upper portion of central bore **195** preferably comprises a smooth transition-surface **204** preferably forming a smoothly sweeping transition between central bore **195** and the circumferential sealing surface **200**, as shown. Preferably, all surfaces contacting exhaust diaphragm **192** are smoothed to reduce contact wear on exhaust diaphragm **192** during operation.

Preferably, valve seat **190** is removably mounted within valve housing **182**, as shown.

Valve seat **190** is preferably sealed to valve housing **182** using at least one fluoroelastomer O-ring **191**, as shown, preferably a Viton O-ring part number 1201T38 by McMaster-Carr of Chicago, IL. Preferably, both valve seat **190** and the overlying exhaust diaphragm **192** are captured within valve housing **182** by DER cover **198**, as shown. Preferably, DER cover **198** is mechanically fastened to valve housing **182**, as shown, preferably using about eight threaded fasteners, preferably type 316 stainless steel socket head cap screws 6-32 thread, 1/2" length, part number 92185A148 by McMaster-Carr of Chicago, IL. Preferably, the entire peripheral edge of exhaust diaphragm **192** is fully sealed to valve housing **182** to fully isolate the exhaust pathway from the ingress of contaminants originating within hazardous diving environment **111**, as shown.

A circumferential plenum chamber **194** is preferably formed within the interior of valve housing **182**, generally below valve seat **190**, and is preferably in fluid communication with outlet duct **186**, as shown.

Preferably, sealing surface **200** is structured and arranged to form at least one pressure seal with exhaust diaphragm **192**, as shown. Sealing surface **200** preferably comprises a plurality of gas-conducting passages **208**, each one structured and arranged to enable passage of the breathing gas from inlet duct **184**, through valve seat **190**, and into plenum chamber **194**, as shown.

Exhaust diaphragm **192** is preferably arranged within valve housing **182** to be in contemporaneous pressure communication with inlet duct **184**, outlet duct **186** and ambient water pressure, the latter preferably by means of aperture openings **196** within removable DER cover **198**, as shown. Preferably, exhaust diaphragm **192** is flexibly movable between at least one flow-blocking position, substantially engaging sealing surface **200**, as shown, and at least one flow-delivery position preferably disengaging sealing surface **200**.

Preferably, while in such flow-blocking position, exhaust diaphragm **192** substantially blocks the passage of the breathing gas through gas-conducting passages **208**, as shown.

Preferably, while in such flow-delivery position, exhaust diaphragm **192** enables the passage of the breathing gas from inlet duct **184** through gas-conducting passages **208** to plenum chamber **194** and outlet duct **186**.

The above-described operation of demand-based valve assembly **180** is preferably enabled by exhausting of the breathing gas by the diver. As the diver exhales, a pressurizing bias force is preferably applied to exhaust diaphragm **192** flexibly moving at least one portion of exhaust diaphragm **192** from the flow-blocking position to the flow-delivery position.

Preferably, each gas-conducting passage **208** comprises a hollow frustoconical aperture, as shown. Preferably, each frustoconical aperture comprises a small inlet diameter **D1** and a larger outlet diameter **D2**, as shown. Preferably, the small inlet diameter **D1** is structured and arranged to minimize unsupported areas of the exhaust diaphragm material when exhaust diaphragm **192** is in the flow-blocking position. This preferably allows the use of relatively thin diaphragm thicknesses, with a corresponding reduction in the required cracking force. The larger outlet diameter **D2** preferably functions to beneficially optimize mass flow through gas-conducting passage **208** and valve seat **190**. Sealing surface **200** preferably comprises a radial arrangement of 102 gas-conducting passages **208** preferably comprising a diameter **D1** of about 0.07 inches and a diameter **D2** formed by a 60° chamfer cut into the underside of valve seat **190** to a depth of about 0.09 inches. Preferably, the upper edge of diameter **D1** is eased by applying a 45° chamfer a depth of about 0.01 inches. Valve seat **190** is preferably constructed from 316 stainless steel. FIG. 6B shows a top view of valve seat **190** of DER **154**. FIG. 6C shows a sectional view through the section 6C-6C of FIG. 6B illustrating preferred arrangements of valve seat **190**. All dimensions within FIG. 6B and 6C are in inches unless noted otherwise.

Preferably, exhaust diaphragm **192** is structured and arranged to generally conform to the surface geometry of sealing surface **200**, when so engaged. More preferably, exhaust diaphragm **192** is molded to substantially match the shape of sealing surface **200** and valve seat **190**, as shown. Preferably, exhaust diaphragm **192** is substantially radially symmetrical about central axis **202**, as shown. Alternate preferred embodiments of exhaust diaphragm **192** comprise a pair of ribs **193**, located axially on the upper (non-sealing) surface of the diaphragm, to allow for eccentric bending, thus reducing the required cracking pressure (at least embodying herein at least one asymmetrical stiffener structured and arranged to structurally stiffen at least one portion of such at least one diaphragm, wherein such asymmetrical structural stiffening reduces the level of pressure forces required to flexibly move such at least one portion of such at least one flexible

diaphragm from such at least one flow-blocking position to such at least one flow-delivery position). As with all soft goods of HEMA **102**, exhaust diaphragm **192** preferably comprises a fluoroelastomer, preferably at least one Viton product. Preferably, exhausted breathing gases exiting outlet duct **186** are subsequently routed through tee fitting **188** to surface-return hose **170** of surface-return subassembly **142**, as shown in FIG. 2.

Preferably, DER **154** is mounted to support plate **157** that is preferably supported from outer shell **128**, as shown. Upon reading the teachings of this specification, those of ordinary skill in the art will now understand that, under appropriate circumstances, considering such issues as intended use, cost, etc., other demand valve arrangements, such as variable pressure swing valves, variable pressure piston valves, swing arm valve assemblies, conventional demand valves, etc., may suffice.

FIG. 10 shows a sectional view, through the section X-X of FIG. 3, illustrating the internal configuration of EDV **146** in normal mode. FIG. 11 shows a sectional view, through the section X-X of FIG. 3 illustrating the internal configuration of EDV **146** in emergency mode. In normal mode, EDV **146** is adapted to exhaust at about 10 inches of H<sub>2</sub>O above ambient pressure. In emergency mode, EDV **146** is adapted to exhaust at about 1 inch of H<sub>2</sub>O above ambient. Preferably, transition between normal mode and emergency mode is user selectable by a diver at depth.

Manual operation preferably occurs by the diver grasping the furthestmost, outmost external portion **210** of the valve assembly and pushing toward dive helmet **103**, while simultaneously turning in a clockwise direction, then releasing. Preferably, the diver can allow all helmet pressure to be relieved through EDV **146**, if the surface return system malfunctions, allowing the diver time to reach safety or to correct the problem causing the off-nominal operation.

When EDV **146** is set to emergency mode, valve-inhibiting member **212** is preferably moved away from O-ring **213** of valve seat **214** allowing one-way exhaust valve **216** to operate freely, (whereas it was previously biased to the closed position by the pressure engagement of the valve-inhibiting member), as shown. Valve-inhibiting member **212** is preferably held under pressure by spring-loaded assembly **218** that can be engaged and disengaged by pushing and rotating bayonet-style lock **220** to at least one closed and open position. By pushing and turning in a first direction, valve-inhibiting member **212** is put into operation and by pushing and turning in a second direction, valve-inhibiting member **212** becomes inoperative.

Preferably, valve-inhibiting member **212** also functions as a pressure relief valve. Preferably, EDV valve **146** is automatically opened by an increase in pressure within dive helmet

**103** above the cracking pressure of valve-inhibiting member **212**. This air pressure overcomes the spring pressure of secondary spring **222** of valve-inhibiting member **212**, thus allowing valve-inhibiting member **212** to be moved away from its closed position long enough for the air pressure in dive helmet **103** to vent to the ambient pressure of the water. Preferably, valve-inhibiting member **212** returns to its closed position when the internal pressure of the helmet can no longer overcome the pressure of secondary spring **222**. Preferably, the automatic venting process of EDV **146** can repeat indefinitely until interrupted by another process.

FIG. 12 shows a schematic diagram, illustrating preferred arrangements of surface-return subassembly **142**, according to the preferred embodiment of FIG. 1. Surface-return subassembly **142** preferably comprises surface-return hose **170** and surface control unit **230**, as shown in both FIG. 1 and FIG. 12. Preferably, surface-return hose **170** conducts exhaust gases from helmet-mounted subassembly **140** to surface control unit **230**, as shown. Testing by applicant indicated that a 0.75 inch inside diameter return hose performs well with capacity for additional flow.

Preferably, surface control unit **230** is configured to provide an indication of diver pressure and backpressure regulator pressure, provisions for testing return gas for hazardous materials **109**, at least one vacuum source for shallow mode operations, and at least one backpressure regulator to hold backpressure on DER **154**.

Preferably, surface control unit **230** comprises at least one reduced-pressure source, more preferably, at least one vacuum pump **250**, most preferably, at least two vacuum pumps **250** for redundancy. Preferably, each vacuum pump **250** is used to maintain vacuum on DER **154** at all times during dive operations. Crossovers between pumps are preferably provided, as shown, to allow for single fault tolerance in the event of a single pump failure. Preferably, each vacuum pump **250** comprises at least one vacuum monitoring gauge **252** adapted to monitor generated vacuum levels. Preferably, vacuum pump **250** is capable of handling at least 62.5 liters per minute with 7.5 pounds per square inch vacuum. Vacuum pump **250** is preferably of oil-less rotary vane design.

Preferably, the reduced pressure produced by vacuum pumps **250** is communicated to surface-return hose **170** through a system of pressure controls and pressure monitors, as shown (at least embodying herein at least one reduced-pressure communicator structured and arranged to establish fluid communication between such at least one reduced-pressure source and such at least one breathing-gas return hose). Preferably, backpressure regulator **254** is structured and arranged to regulate levels of reduced atmospheric pressure communicated between vacuum pumps **250** and surface-return hose **170**, as shown.

Preferably, surface control unit **230** further comprises at least one pressure indicator, more preferably at least one duplex pressure gauge **256** structured and arranged to indicate at least one pneumatic reference pressure, and at least one indication of the operating pressure at DER **154**. More specifically, duplex pressure gauge **256** preferably displays pneumofathometer reference pressure and pressure at backpressure regulator **254**, as shown. Preferably, the difference between the two measurements indicates the bias held by backpressure regulator **254**. Preferably, duplex pressure gauge **256** is capable of displaying -30inHg to 150psi. A preferred gauge suitable for use as duplex pressure gauge **256** includes the Weksler model BB14P by Weksler Glass Thermometer Corp. of Charlottesville, VA.

Preferably, surface control unit **230** further comprises at least one breathing-gas monitoring unit **260** structured and arranged to monitor the exhausted breathing gas of the breathing environment for levels of hazardous material **109**. Preferably, breathing-gas monitor comprises at least one breathing-gas sampling component **262** structured and arranged to sample the breathing gas of the at least one breathing environment, as shown. Preferably, gas samples are taken at sampling ports located between backpressure regulator **254** and vacuum pumps **250**, as shown. Preferably, breathing-gas monitoring unit **260** further comprises at least one measurement component **264** structured and arranged to measure the levels of the at least one hazardous material of the sampled breathing gas to determine if the levels of the at least one hazardous material fall within a preset range. In addition, breathing-gas monitoring unit **260** preferably comprises at least one hazardous-condition indicator **266** designed to indicate if the levels of hazardous material **109** within the breathing environment has exceeded the preset range. If such a condition were to occur, hazardous-condition indicator **266** would preferably provide an indication to the surface tender/operator to allow risk-mitigating steps to be taken. Upon reading the teachings of this specification, those of ordinary skill in the art will now understand that, under appropriate circumstances, considering such issues as intended use, hazardous environment, etc., other monitoring arrangements, such as in-helmet chemical detectors, water sampling devices, etc., may suffice.

FIG. 13 shows a schematic diagram illustrating a preferred method of using a retrofitted underwater dive system (HMRSEDS **300**) to avoid health hazards relating to special diving operations, according to a preferred method of the present invention. In accordance with the above-described preferred embodiments of hazardous-environmental diving system **100**, there is provided method **280**, related to use of a retrofitted existing underwater dive system **101** to avoid health hazards relating to at least one diver operating in waters needed to be essentially uncontaminated, such method comprising the following steps. In initial step **282**, an existing

underwater dive system **101** is identified to be used in specialized diving operations. Such specialized diving operation may preferably include the carrying out of maintenance work within a municipal reservoir where biological contaminants conveyed within the diver's exhausted breath may create a health hazard within the body of water in which the diver operates.

5 Preferably, existing underwater dive system **101** is modified by removing the in-water exhaust subsystem **114**, and adding RSE assembly **104** (at least embodying herein at least one surface-return exhaust subsystem) to enable the return of breathing gas from the breathing environment of dive helmet **103** to the surface, as indicated in preferred step **284**. Thus, use of such at least one retrofitted existing commercial dive system in such waters assists in avoiding  
10 water contamination relating to such exhaust breathing gas.

FIG. 14 shows a flow diagram illustrating preferred method **350** related to retrofitting existing underwater dive system **101**, in accordance with the above-described preferred embodiments of hazardous-environmental diving system **100**, according to a preferred method of the present invention. In the initial preferred step **352** of method **350**, at least one existing  
15 underwater dive system **101** is identified. Next, as indicated in preferred step **354**, potential hazardous-material-caused failure points, which may result in injurious introduction of at least one hazardous material **109** into the diver's breathing environment during the operational duration, are preferably identified within existing underwater dive system **101**. This may preferably include analysis and identification of materials vulnerable to direct chemical  
20 degradation and chemical infiltration. In preferred step **356**, at least one risk-mitigating modification to existing underwater dive system **101** is designed, such at least one risk-mitigating modification structured and arranged substantially mitigate risks associated with the hazardous-material-caused failure points identified in step **354**. Next, as indicated in preferred step **358** at least one retrofit kit is provided, preferably containing materials and procedures  
25 required to implement such risk-mitigating modifications to existing underwater dive system **101** to produce HMRSEDS **300**, preferably comprising HEMA **102**. In preferred step **358**, at least one of the risk-mitigating modifications comprises the replacement of at least one existing chemically-sensitive component with at least one flourelastomer replacement.

Although applicant has described applicant's preferred embodiments of this invention, it  
30 will be understood that the broadest scope of this invention includes modifications such as diverse shapes, sizes, and materials. Such scope is limited only by the below claims as read in connection with the above specification. Further, many other advantages of applicant's invention will be apparent to those skilled in the art from the above descriptions and the below claims.

## WHAT IS CLAIMED IS:

- 1) A method related to retrofitting at least one existing underwater dive system to enhance the safety of at least one diver operating in waters containing at least one hazardous material, such at least one existing underwater dive system comprising at least one existing dive helmet, at  
5 least one existing surface-supplied breathing-gas subsystem, at least one existing in-water exhaust subsystem, and at least one breathing environment available to the at least one diver, said method comprising the steps of:
- a) identifying at least one such existing underwater dive system comprising the at least one existing dive helmet, the at least one existing surface-supplied breathing-gas  
10 subsystem, and the at least one in-water exhaust subsystem;
- b) identifying, within the at least one existing underwater dive system, potential hazardous-material-caused failure points that result in at least one injurious introduction of at least one hazardous material into the at least one breathing environment during at least one operational duration;
- 15 c) designing at least one risk-mitigating modification to such at least one existing underwater dive system, such at least one risk-mitigating modification being structured and arranged to substantially mitigate risks associated with such hazardous-material-caused failure points identified to occur within the at least one operational duration;
- 20 d) providing at least one retrofit kit comprising materials and procedures required to implement such at least one risk-mitigating modification to such at least one existing underwater dive system.
- 2) The method according to Claim 1 wherein the step of providing at least one risk-mitigating modification further comprises the step of integrating such at least one risk-mitigating  
25 modification into such at least one existing underwater dive system.
- 3) The method according to Claim 1 wherein the step of providing at least one risk-mitigating modification further comprises the step of:
- a) providing at least one soft-goods replacement for at least one existing hazardous-material-susceptible soft good experiencing exposure to the at least one hazardous  
30 material during the at least one operational duration;
- b) wherein the at least one soft-goods replacement comprises at least one hazardous-material-resistant composition; and
- c) wherein, within the at least one operational duration, such at least one hazardous-material-resistant composition is substantially resistant to

- i) degraded physical performance by contact with the at least one hazardous material, and
  - ii) transmission of hazardous quantities of the at least one hazardous material into the at least one breathing environment by permeation of the at least one hazardous material through such hazardous-material-resistant composition.
- 5 4) The method according to Claim 3 wherein such at least one hazardous-material-resistant composition comprises at least one fluoroelastomer.
- 5) The method according to Claim 3 wherein the step of providing such at least one soft-goods replacement further comprises the step of integrating such at least one soft-goods replacement  
10 within such at least one existing underwater dive system.
- 6) The method according to Claim 3 wherein the step of providing at least one risk-mitigating modification further comprises the steps of:
  - a) providing at least one in-water-exhaust disabler to disable the at least one existing in-water exhaust subsystem;
  - 15 b) providing at least one surface-return exhaust subsystem structured and arranged to exhaust breathing gas from the at least one breathing environment of the at least one existing dive helmet to the surface;
  - c) wherein at least one entry path for inhalable amounts of the at least one hazardous material may be removed.
- 20 7) The method according to Claim 6 wherein the surface-return exhaust subsystem comprises:
  - a) at least one breathing-gas return hose structured and arranged to return breathing gas to the surface;
  - b) at least one demand-based exhaust regulator structured and arranged to regulate, essentially on demand, exhausting of the breathing gas from the at least one breathing  
25 environment of the at least one existing dive helmet to such at least one breathing-gas return hose; and
  - c) at least one exhaust coupler structured and arranged to operably couple such at least one demand-based exhaust regulator to the at least one breathing environment of the at least one existing dive helmet;
  - 30 d) wherein at least one demand-based exhaust pathway may be established between the at least one breathing environment of the at least one existing dive helmet and the surface.
- 8) The method according to Claim 7 wherein the surface-return exhaust subsystem further comprises:

- a) between such at least one exhaust coupler and such at least one demand-based exhaust regulator, at least one over-pressure relief valve structured and arranged to relieve over pressures within the at least one breathing environment within the at least one existing dive helmet; and
- 5 b) between such at least one exhaust coupler and such at least one demand-based exhaust regulator, at least one gas-flow control valve structured and arranged to control the routing of the breathing gas between the at least one breathing environment of the at least one existing dive helmet, such at least one demand-based exhaust regulator, and such at least one breathing-gas return hose;
- 10 c) wherein such at least one gas-flow control valve comprises
- i) at least one first flow setting to enable exhausting of the breathing gas from the at least one breathing environment of the at least one existing dive helmet to such at least one demand-based exhaust regulator,
- 15 ii) at least one second flow setting to enable exhausting of the breathing gas from the at least one breathing environment of the at least one existing dive helmet directly to such at least one breathing-gas return hose without passage through such at least one demand-based exhaust regulator, and
- 20 iii) at least one third flow setting to enable exhausting of the breathing gas from the at least one breathing environment of the at least one existing dive helmet substantially entirely through such at least one over-pressure relief valve by preventing exhausting of the breathing gas through such at least one demand-based exhaust regulator and such at least one breathing-gas return hose.
- 9) The method according to Claim 8 wherein the step of providing such at least one surface-return exhaust subsystem further comprises the steps of:
- 25 a) providing at least one reduced-pressure source structured and arranged to provide at least one source of reduced atmospheric pressure;
- b) providing at least one reduced-pressure communicator structured and arranged to establish fluid communication between such at least one reduced-pressure source and such at least one breathing-gas return hose; and
- 30 c) providing at least one back-pressure regulator structured and arrange to regulate levels of reduced atmospheric pressure communicated between such at least one reduced-pressure source and such at least one breathing-gas return hose.
- 10) The method according to Claim 9 wherein the step of providing such at least one surface-return exhaust subsystem further comprises the step of:

- a) providing at least one pressure indicator structured and arranged to indicate
- i) at least one pneumatic reference pressure, and
  - ii) at least one indication of pressure at such at least one demand-based exhaust regulator; and
- 5 b) providing at least one breathing-gas monitor structured and arranged to monitor the breathing gas of the at least one breathing environment for levels of the at least one hazardous material;
- c) wherein such at least one breathing-gas monitor comprises
- 10 i) at least one breathing-gas sampling component structured and arranged to sample the breathing gas of the at least one breathing environment,
  - ii) at least one measurement component structured and arranged to measure the levels of the at least one hazardous material of the sampled breathing gas to determine if the levels of the at least one hazardous material fall within a preset range, and
  - 15 iii) at least one hazardous-condition indicator structured and arranged to indicate to at least one system operator if the levels of the at least one hazardous material exceed the preset range.
- 11) The method according to Claim 7 wherein the step of providing such at least one surface-return exhaust subsystem further comprises the step of integrating such at least one surface-return exhaust subsystem within such at least one existing underwater dive system.
- 20 12) The method according to Claim 1 wherein the step of providing at least one risk-mitigating modification further comprises the step of:
- 25 a) providing at least one optical-faceplate covering structured and arranged to substantially cover at least one existing optical faceplate of the at least one existing dive helmet;
  - b) wherein, within the at least one operational duration, such at least one optical-faceplate covering comprises at least one hazardous-material-resistant material substantially resistant to
    - 30 i) degraded physical performance by contact with the at least one hazardous material, and
    - ii) introduction of hazardous levels of the at least one hazardous material into the at least one breathing environment by permeation of the at least one hazardous material through such at least one hazardous-material-resistant material; and

- c) wherein such at least one hazardous-material-resistant material comprises sufficient transparency as to maintain a level of optical viewing through the at least one existing optical faceplate.
- 5 13) The method according to Claim 12 wherein such at least one optical faceplate cover comprises at least one surface lamination of at least one glass material.
- 14) The method according to Claim 13 wherein the step of providing such at least one optical faceplate cover further comprises the step of integrating such at least one optical faceplate cover within such at least one existing underwater dive system.
- 10 15) The method according to Claim 1 wherein the step of providing at least one risk-mitigating modification further comprises the step of:
- a) providing at least one chemical-resistant hose covering structured and arranged to cover the at least one existing breathing-gas supply hose;
- b) wherein the at least one chemical-resistant hose covering is structured and arranged to maintain the functional integrity of the at least one existing breathing-gas supply hose,
- 15 within the at least one operational duration.
- 16) The method according to Claim 15 wherein the step of providing at least one mitigating modification further comprises the steps of modifying such at least one existing breathing-gas supply hose to comprise such at least one chemical-resistant covering.
- 20 17) The method according to Claim 1 wherein the step of providing at least one risk-mitigating modification further comprises the step of:
- a) providing at least one helmet coating usable to coat at least one possibly-permeable outer-shell-portion of the at least one existing dive helmet;
- b) wherein such at least one helmet-coating is structured and arranged to reduce transmission of hazardous quantities of the at least one hazardous material into the at
- 25 least one breathing environment by reducing contact interaction between the at least one hazardous material and the at least one possibly-permeable outer-shell-portion of the at least one existing dive helmet.
- 18) The method according to Claim 1 wherein the step of providing at least one risk-mitigating modification further comprises the step of:
- 30 a) providing at least one replacement sealant structured and arranged to replace existing sealants of the at least one existing underwater dive system;
- b) wherein such at least one replacement sealant is structured and arranged to reduce transmission of hazardous quantities of the at least one hazardous material into the at least one breathing environment of the at least one existing dive helmet by

permeation of the at least one hazardous material through such at least one replacement sealant.

- 19) The method according to Claim 18 wherein such at least one replacement sealant comprises at least one room-temperature-cured fluoroelastomer-based composition.
- 5 20) The method according to Claim 19 wherein the step of providing at least one risk-mitigating modification further comprises the step of integrating such at least one replacement sealant within such at least one existing underwater dive system.
- 21) A kit system related to retrofitting at least one existing underwater dive system to enhance the safety of at least one diver operating in waters containing at least one hazardous material, such  
10 at least one existing underwater dive system comprising at least one existing dive helmet, at least one existing surface-supplied breathing-gas subsystem, at least one existing in-water exhaust subsystem, and at least one breathing environment available to the at least one diver, said system comprising:
- a) at least one soft-goods replacement structured and arranged to replace at least one  
15 existing hazardous-material-susceptible soft good experiencing exposure to the at least one hazardous material during the at least one operational duration;
- b) wherein the at least one soft-goods replacement comprises at least one hazardous-material-resistant composition; and
- c) wherein, within the at least one operational duration, such at least one hazardous-  
20 material-resistant composition is substantially resistant to
- i) degraded physical performance by contact with the at least one hazardous material, and
- ii) transmission of hazardous quantities of the at least one hazardous material into  
25 the at least one breathing environment by permeation of the at least one hazardous material through such hazardous-material-resistant composition.
- 22) The kit system according to Claim 21 wherein said at least one hazardous-material-resistant composition comprises at least one fluoroelastomer.
- 23) The kit system according to Claim 21 further comprising:
- a) at least one in-water-exhaust disabler structured and arranged to disable the at least  
30 one existing in-water exhaust subsystem; and
- b) at least one surface-return exhaust subsystem structured and arranged to exhaust breathing gas from the at least one breathing environment of the at least one existing dive helmet to the surface;

- c) wherein at least one entry path for inhalable amounts of the at least one hazardous material may be removed.
- 24) The kit system according to Claim 23 wherein said surface-return exhaust subsystem comprises:
- 5 a) at least one breathing-gas return hose structured and arranged to return breathing gas to the surface;
- b) at least one demand-based exhaust regulator structured and arranged to regulate, essentially on demand, exhausting of the breathing gas from the at least one breathing environment of the at least one existing dive helmet to said at least one breathing-gas return hose; and
- 10 c) at least one exhaust coupler structured and arranged to operably couple such at least one demand-based exhaust regulator to the at least one breathing environment of the at least one existing dive helmet;
- d) wherein at least one demand-based exhaust pathway may be established between the
- 15 at least one breathing environment of the at least one existing dive helmet and the surface.
- 25) The kit system according to Claim 24 wherein said surface-return exhaust subsystem further comprises:
- a) between said at least one exhaust coupler and said at least one demand-based exhaust
- 20 regulator, at least one over-pressure relief valve structured and arranged to relieve over pressures within the at least one breathing environment within the at least one existing dive helmet; and
- b) between said at least one exhaust coupler and said at least one demand-based exhaust regulator, at least one gas-flow control valve structured and arranged to control the
- 25 routing of the breathing gas between the at least one breathing environment of the at least one existing dive helmet, said at least one demand-based exhaust regulator, and said at least one breathing-gas return hose;
- c) wherein said at least one gas-flow control valve comprises
- i) at least one first flow setting to enable exhausting of the breathing gas from the
- 30 at least one breathing environment of the at least one existing dive helmet to said at least one demand-based exhaust regulator,
- ii) at least one second flow setting to enable exhausting of the breathing gas from the at least one breathing environment of the at least one existing dive helmet

directly to said at least one breathing-gas return hose essentially without passage through said at least one demand-based exhaust regulator, and

- iii) at least one third flow setting to enable exhausting of the breathing gas from the at least one breathing environment of the at least one existing dive helmet substantially entirely through said at least one over-pressure relief valve by preventing exhausting of the breathing gas through said at least one demand-based exhaust regulator and said at least one breathing-gas return hose.

5

26) The kit system according to Claim 25 wherein said at least one surface-return exhaust subsystem further comprises:

10

- a) at least one reduced-pressure source structured and arranged to provide at least one source of reduced atmospheric pressure;
- b) at least one reduced-pressure communicator structured and arranged to establish fluid communication between said at least one reduced-pressure source and said at least one breathing-gas return hose; and

15

- c) at least one back-pressure regulator structured and arranged to regulate levels of reduced atmospheric pressure communicated between said at least one reduced-pressure source and said at least one breathing-gas return hose.

27) The kit system according to Claim 26 wherein said at least one surface-return exhaust subsystem further comprises:

20

- a) at least one pressure indicator structured and arranged to indicate
- i) at least one pneumatic reference pressure, and
- ii) at least one indication of operating pressure at said at least one demand-based exhaust regulator; and

25

- b) at least one breathing-gas monitor structured and arranged to monitor the breathing gas of the at least one breathing environment for levels of the at least one hazardous material;

30


- c) wherein said at least one breathing-gas monitor comprises
- i) at least one breathing-gas sampling component structured and arranged to sample the breathing gas of the at least one breathing environment,
- ii) at least one measurement component structured and arranged to measure the levels of the at least one hazardous material of the sampled breathing gas to determine if the levels of the at least one hazardous material fall within a preset range, and

- d) at least one hazardous-condition indicator structured and arranged to indicate if the levels of the at least one hazardous material exceed the preset range.
- 28) The kit system according to Claim 25 further comprising:
- 5 a) at least one optical-faceplate cover structured and arranged to substantially cover at least one existing optical faceplate of the at least one existing dive helmet;
- b) wherein, within the at least one operational duration, such at least one optical-faceplate cover comprises at least one hazardous-material-resistant material substantially resistant to
- 10 i) degraded physical performance by contact with the at least one hazardous material, and
- ii) introduction of hazardous levels of the at least one hazardous material into the at least one breathing environment by permeation of the at least one hazardous material through said at least one hazardous-material-resistant material; and
- c) wherein such at least one hazardous-material-resistant material comprises sufficient
- 15 transparency as to maintain a level of optical viewing through the at least one existing optical faceplate.
- 29) The kit system according to Claim 28 wherein said at least one optical faceplate cover comprises at least one glass material.
- 30) The kit system according to Claim 25 further comprising:
- 20 a) at least one chemical-resistant hose covering structured and arranged to cover the at least one existing breathing-gas supply hose;
- b) wherein said at least one chemical-resistant hose covering is structured and arranged to maintain the functional integrity of the at least one existing breathing-gas supply hose, within the at least one operational duration.
- 25 31) The kit system according to Claim 25 further comprising:
- a) at least one helmet coating structured and arranged to coat at least one possibly-permeable outer-shell-portion of the at least one existing dive helmet;
- b) wherein said at least one helmet-coating is further structured and arranged to reduce transmission of hazardous quantities of the at least one hazardous material into the at
- 30 least one breathing environment by reducing contact interaction between the at least one hazardous material and the at least one possibly-permeable outer-shell-portion of the at least one existing dive helmet.
- 32) The kit system according to Claim 25 further comprising:

- a) at least one replacement sealant structured and arranged to replace existing sealants of the at least one existing commercial dive system;
- b) wherein said at least one replacement sealant is structured and arranged to reduce transmission of hazardous quantities of the at least one hazardous material into the at least one breathing environment of the at least one existing dive helmet by permeation of the at least one hazardous material through such at least one replacement sealant.
- 5
- 33) The kit system according to Claim 32 wherein said at least one replacement sealant comprises at least one room-temperature-cured fluoroelastomer-based composition.
- 10 34) The kit system according to Claim 24 wherein said at least one demand-based exhaust regulator comprises:
- a) at least one demand-based valve assembly structured and arranged to control, essentially on demand, passage of the breathing gas through said at least one demand-based exhaust regulator;
- 15 b) at least one valve housing structured and arranged to house said at least one demand-based valve assembly;
- c) at least one inlet duct structured and arranged to inlet the breathing gas, exhausted from the at least one breathing environment of the at least one existing dive helmet, to said at least one demand-based valve assembly; and
- 20 d) at least one outlet duct structured and arranged to outlet the breathing gas, from said at least one demand-based valve assembly, to said at least one breathing-gas return hose;
- e) wherein said at least one demand-based valve assembly comprises
- 25 i) disposed between said at least one inlet duct and said at least one outlet duct, at least one valve seat, comprising a plurality of gas-conducting passages, structured and arranged to enable passage of the breathing gas therethrough, and
- ii) in at least one superimposed placement adjacent said at least one valve seat, at least one diaphragm structured and arranged to be in pressure communication with said at least one inlet duct, said at least one outlet duct and ambient water pressure;
- 30 f) wherein said at least one diaphragm is flexibly movable between at least one flow-blocking position substantially engaging said at least one valve seat and at least one flow-delivery position disengaging said at least one valve seat;

- g) wherein, while in such at least one flow-blocking position, said at least one diaphragm substantially blocks the passage of the breathing gas through said plurality of gas-conducting passages;
- h) wherein, while in such at least one flow-delivery position, said at least one diaphragm enables the passage of the breathing gas from said at least one inlet duct through said plurality of gas-conducting passages to said at least one outlet duct; and
- i) wherein exhausting of the breathing gas from the at least one breathing environment applies a pressurizing bias force to said at least one diaphragm flexibly moving at least one portion of said at least one flexible diaphragm from such at least one flow-blocking position to such at least one flow-delivery position.
- 35) The kit system according to Claim 34 wherein said at least one valve seat comprises:
- a) at least one central bore structured and arranged to be in fluid communication with said at least one inlet duct, said at least one central bore comprising at least one central axis;
- b) extending radially outward of said at least one central bore, at least one circumferential sealing surface structured and arranged to form at least one pressure seal with said at least one diaphragm; and
- c) at least one smooth-sweep transition-surface structured and arranged to provide at least one smoothly sweeping transition between said at least one central bore and said at least one circumferential sealing surface;
- d) wherein said plurality of gas-conducting passages are located within said at least one circumferential sealing surface.
- 36) The kit system according to Claim 35 wherein:
- a) each one of said plurality of gas-conducting passages comprises a hollow frustoconical aperture;
- b) each said hollow frustoconical aperture comprises
- i) at least one inlet diameter structured and arranged to minimize unsupported areas of said at least one diaphragm when said at least one diaphragm is in such at least one flow-blocking position, and
- ii) at least one outlet diameter structured and arranged to beneficially optimize mass flow through said at least one valve seat.

- 37) The kit system according to Claim 36 wherein said at least one diaphragm is further structured and arranged to generally conform to said at least one circumferential sealing surface when engaged with said at least one circumferential sealing surface.
- 38) The kit system according to Claim 37 wherein said at least one diaphragm further  
5 comprises:
- a) at least one asymmetrical stiffener structured and arranged to structurally stiffen at least one portion of said at least one diaphragm;
  - b) wherein such asymmetrical structural stiffening reduces the level of pressure forces required to flexibly move such at least one portion of said at least one  
10 flexible diaphragm from such at least one flow-blocking position to such at least one flow-delivery position.
- 39) A method, related to use of at least one existing commercial dive system to avoid health hazards relating to at least one diver operating in waters needed to be essentially uncontaminated, such at least one existing commercial dive system comprising at least one  
15 existing dive helmet, at least one existing demand-based breathing-gas supply subsystem, at least one existing in-water exhaust subsystem, and at least one breathing environment available to the at least one diver, said method comprising the steps of:
- a) identifying at least one such existing commercial dive system comprising the at least one existing dive helmet, the at least one existing demand-based breathing-gas supply  
20 subsystem, and the at least one in-water exhaust subsystem; and
  - b) modifying such at least one such existing commercial dive system by
    - i) providing at least one in-water-exhaust disabler to disable the at least one existing in-water exhaust subsystem, and
    - ii) providing at least one surface-return exhaust subsystem structured and  
25 arranged to exhaust breathing gas from the at least one breathing environment of the at least one existing dive helmet to the surface;
  - c) wherein use of such at least one modified existing commercial dive system in such waters assists in avoiding water contamination relating to such exhaust breathing gas.






FIG. 2




FIG. 3





FIG. 4






FIG. 6A




FIG. 6B




FIG. 6C




FIG. 7




FIG. 8






FIG. 9








FIG. 13




FIG. 14